

ARCHITECTURAL LIGHTING

Introducing the ICARUS-S



The **ICARUS-S** is an efficient decorative **Fire Rated** recessed LED downlight luminaire suitable for accent and area lighting in offices, schools and public areas - small size best suited for rest room and accent lighting.



Consult SA (PTY) LTD



SABS
ISO 9001

ICARUS-S



Product Features

- Fire Rated
- Housing in die-cast aluminium - powder coated with structured finish
- Super-purity aluminium reflector with two beam angle options
- Good heat dissipation due to cast aluminium heat sink
- Remote LED driver
- Available in CCT 3000K and 4000K - additional specialised colours available on request
- Available in CRI Ra > 80 and Ra > 90
- Options include DALI dimming, emergency backup and Bluetooth mesh control
- LED life L₈₀B₁₀ - 50 000 hours
- Driver life F₁₀ - 100 000 hours
- Supply - 220-240V 50-60Hz PF > 0.95
- Surge current (flicker) < 5%
- 5 year guarantee



Luminaire Wattage	Luminaire Output (Lumens)	Colour Temperature	Efficacy lm/W	Ra (CRI)	Reference Code
6W (250mA)	680	3000K	113	>80	LLC-ICA-S-6W-3K
6W (250mA)	700	4000K	116	>80	LLC-ICA-S-6W-4K



Consult SA (PTY) LTD



SABS
ISO 9001