

ACCENT LIGHTING



Introducing the PANDORA-S



PANDORA-S is a track-mounted flexible spotlight delivering an ideal lighting system for display lighting, commercial shopping malls, restaurants and especially ideal for retail displays.



Consult SA (PTY) LTD



SABS
ISO 9001

PANDORA-S




Product Features

- Housing in extruded aluminium, ends of die-cast aluminium - powder coated with structured finish
- Front ring in thermoplastic
- Super-purity Miro reflector with three beam angle options
- Built-In LED driver
- Available in CCT 3000K and 4000K - additional specialised colours available on request
- Available in CRI Ra > 80 and Ra > 90
- Options include DALI dimming, Bluetooth mesh control and emergency battery backup.
- LED life L₈₀B₁₀ - 50 000 hours
- Driver life F₁₀ - 100 000 hours
- Supply - 220-240V 50-60Hz PF > 0.95
- Surge current (flicker) < 5%
- 5 year guarantee



 **122 lm/W**

The following lens optic options are also available - Oval 57° x 30°, Medium 32°, Flood 47° and Wide Flood 53°



Efficacy Rating

-  **PREMIUM RANGE** >140 lm/W
-  **MID RANGE** 120 - 140 lm/W
-  **ECO RANGE** 100 - 120 lm/W

Luminaire Wattage	Luminaire Output (Lumens)	Colour Temperature	Efficacy lm/W	RA (CRI)	Reference Code
14W (350mA)	1 550	3000K	111	>80	LLC-PNA-S-14W-WHT-43-3K
14W (350mA)	1 700	4000K	121	>80	LLC-PNA-S-14W-WHT-43-4K
21W (500mA)	2 130	3000K	101	>80	LLC-PNA-S-21W-WHT-43-3K
21W (500mA)	2 350	4000K	112	>80	LLC-PNA-S-21W-WHT-43-4K
23W (600mA)	2 560	3000K	111	>80	LLC-PNA-S-23W-WHT-43-3K
23W (600mA)	2 800	4000K	122	>80	LLC-PNA-S-23W-WHT-43-4K
28W (700mA)	2 940	3000K	105	>80	LLC-PNA-S-28W-WHT-43-3K
28W (700mA)	3 220	4000K	115	>80	LLC-PNA-S-28W-WHT-43-4K



Consult SA (PTY) LTD



SABS
ISO 9001